



HIGH
PERFORMANCE



INDUSTRIAL
DURABILITY



RAPID COATINGS

RAPID PAINTS



**DRIES FAST.
LASTS LONG.**

Provides fast drying, excellent adhesion and high durability on various surfaces such as metal, wood, plastic and concrete.



FAST
DRYING



STRONG
ADHESION



HIGH
DURABILITY



WEATHER & UV
RESISTANCE



EASY
APPLICATION



STEEL
STRUCTURES



MACHINERY &
EQUIPMENT



METAL, WOOD &
CONCRETE SURFACES



CONTAINER &
TANKS



INDUSTRIAL
FACILITIES



COST EFFECTIVE
SOLUTION



CORROSION
RESISTANCE



LONG-LASTING
PERFORMANCE



HIGH
PERFORMANCE



MAXIMUM
PROTECTION



FAST DRYING

Dries in a short time and provides time savings with its high strength.



HIGH DURABILITY

Excellent resistance to mechanical impacts, abrasion, chemicals, and weather conditions.



EASY APPLICATION

Can be easily and uniformly applied with roller, brush or spray.



GLOSSY APPEARANCE

Provides a smooth, glossy and aesthetic surface finish.

OUR PRODUCTS	FEATURES	PACKAGING
	RAPID TOPCOAT PAINT - Fast drying - High gloss and smooth finish - Resistant to abrasion and chemicals - Suitable for indoor and outdoor use - Strong adhesion on all metal surfaces	 15 kg  2.5 kg  0.850 kg
	RAPID PRIMER - Fast drying primer paint - Superior protection against corrosion - Prepares an ideal surface for topcoat - Suitable for indoor and outdoor use - High bonding strength	 15 kg  2.5 kg  0.850 kg
	RAPID ANTI-RUST PAINT - Rust preventive formula - Excellent corrosion protection on metal surfaces - Fast drying, provides a strong adhesion - Prepares an ideal surface for topcoat - Suitable for indoor and outdoor use	 15 kg  2.5 kg  0.850 kg
	RAPID MATT PAINT - Matt finish - Aesthetic appearance for interior and exterior use - Resistant to abrasion and chemicals - Easy to clean - Suitable for indoor and outdoor use	 15 kg  2.5 kg  0.850 kg
	RAPID HAMMER FINISH PAINT - Textured (hammer) decorative appearance - High adhesion and corrosion resistance - Resistant to water, impact and chemicals - Provides a decorative coating on metal surfaces - Suitable for indoor and outdoor use	 15 kg  2.5 kg  0.850 kg

Note: Prices are for reference only and do not include application, transportation or other additional services.



TECHNICAL SPECIFICATIONS

Binder Type	: Alkyd Resin
Appearance	: Glossy / Matt
Solid Content (by weight)	: 75 ± 2%
Viscosity	: 120 ± 15 sn (Ford 4)
Drying Time (20°C)	: Dust Free: 2 – 5 min Touch Dry: 5 – 18 min
Application Method	: Brush, Roller, Spray
Thinner	: 15 – 25% (Rapid Thinner)
Theoretical Coverage	: 7 – 9 m²/L per coat
Number of Coats	: 1 – 2 coats
Recoating Time	: 24 hours



APPLICATION AREAS

	Metal structures
	Machinery and equipment
	Steel constructions
	Containers, tanks and silos
	Automotive and transportation vehicles
	Industrial facilities and factories
	Doors, windows, railings and steel structures
	Suitable for indoor and outdoor use



APPLICATION INSTRUCTIONS

The surface must be clean, dry and free from oil, dirt and dust.

Remove old paint and loose parts.

Use thinner for surface cleaning if necessary.

For roller, brush or spray application, dilute with the recommended thinner.

Stir the product well before use.

It is recommended to apply 1 – 2 coats with an interval of 24 hours between coats.

Ideal application temperature: 10°C – 30°C.