



LIQUID WATERPROOFING GROUP

-  SEAMLESS WATERPROOFING
-  ELASTIC STRUCTURE
-  UV RESISTANT

LIQUID APPLIED WATERPROOFING SYSTEMS

Provides excellent waterproofing in terraces, roofs, balconies, wet areas and all concrete surfaces with its high adhesion, flexible structure and long-lasting durability.



AREAS OF APPLICATION



TERRACE



ROOF



BATHROOM



POOL



WATER TANK



CAR PARK



INDUSTRIAL FACILITIES

2026
PRODUCT CATALOG

*Stronger Buildings
Safer Lives*

SURFACE WATERPROOFING LIQUID WATERPROOFING SYSTEMS

Provides an ideal solution for waterproofing roofs, terraces, balconies, wet areas, foundations and all concrete surfaces.



1K WATERPROOF

SINGLE COMPONENT LIQUID WATERPROOFING COATING



1K liquid waterproofing membrane is a ready-to-use, single component, high-performance coating that provides long-lasting waterproofing on all kinds of surfaces.

TECHNICAL SPECIFICATIONS

Chemical Structure	Acrylic resin based
Color	White, Grey
Density	1.30 ± 0.10 g/cm³
Solid Content	%65 ± 2
Viscosity (25°C)	90 – 110 KU
Drying Time	Surface dry: 2–3 hours Full cure: 24 hours
Application Temperature	+5°C / +35°C
Consumption	1.0 – 1.5 kg/m² (2 coats)
Shelf Life	12 months
Packaging	20 kg

ADVANTAGES

- Ready to use
- UV resistant
- High adhesion
- Elastic and crack-bridging
- Water vapor permeable (breathable)
- Suitable for indoor and outdoor use
- Environmentally friendly

AREAS OF USE

- Roofs and terraces
- Balconies
- Bathrooms
- Kitchens and wet areas
- Foundations and retaining walls
- Concrete, plaster, screed
- Metal and wooden surfaces

AVAILABLE COLORS



APPLICATION STEPS

- 1 SURFACE PREPARATION**
The surface must be clean, dry and free from dust, oil and loose materials.
- 2 PRIMER APPLICATION**
Apply Vorexa primer, allow to dry according to the technical data.
- 3 FIRST COAT APPLICATION**
Apply the first coat with a roller, brush or airless sprayer.
- 4 SECOND COAT APPLICATION**
After the first coat dries, apply the second coat.
- 5 RESULT**
A seamless, durable and waterproof surface.

2K WATERPROOF

TWO COMPONENT LIQUID WATERPROOFING COATING



2K waterproofing is a high-performance, two component, flexible and durable waterproofing coating. It provides excellent adhesion on concrete, screed, ceramic, metal and many other surfaces.

SET CONTENT

**A COMPONENT (Resin) +
B COMPONENT (Hardener)**

TECHNICAL SPECIFICATIONS

Chemical Structure	Polyurethane based
Color	Grey (other colors optional)
Mixing Ratio (A:B)	4 : 1 (weight)
Density (A+B)	1.40 ± 0.10 g/cm³
Pot Life (25°C)	30 – 45 minutes
Curing Time	Light traffic: 24 hours Full cure: 7 days
Application Temperature	+5°C / +30°C
Consumption	1.5 – 2.0 kg/m² (2–3 coats)
Adhesion Strength	≥ 2.0 N/mm²
Elasticity	≥ 300%
Shelf Life	12 months
Packaging	20 kg set (A: 16 kg + B: 4 kg)


ADVANTAGES

- High mechanical strength
- Excellent chemical resistance
- Flexible and crack-bridging
- Seamless application
- Suitable for heavy traffic
- Indoor and outdoor use
- Long-lasting and durable

AREAS OF USE

- Terraces and roofs
- Balconies
- Water tanks
- Swimming pools
- Bathrooms and wet areas
- Industrial floors
- Parking areas and bridges
- Metal and prefabricated surfaces

AVAILABLE COLORS



APPLICATION STEPS

- 1 SURFACE PREPARATION**
The surface must be clean, dry and free from dust, oil and loose materials.
- 2 PRIMER APPLICATION**
Apply Vorexa primer, allow to dry according to the technical data.
- 3 MIXING COMPONENTS**
Mix Component A and B homogeneously.
- 4 FIRST COAT APPLICATION**
Apply with a roller, brush or airless sprayer.
- 5 SECOND COAT APPLICATION**
After the first coat dries, apply the second coat.
- 6 RESULT**
A seamless, resistant and waterproof surface.

*Stronger Surfaces
Safer Lives*

SPECIAL PRODUCTS

HIGH QUALITY – SUPERIOR PROTECTION – LONG LASTING SOLUTIONS

- WATER BASED
- SUPERIOR PROTECTION
- UV RESISTANT
- ELASTIC STRUCTURE
- EASY APPLICATION
- ECO FRIENDLY